

(19) World Intellectual Property Organization
International Bureau



18 JUL 2004



(43) International Publication Date
31 July 2003 (31.07.2003)

PCT

(10) International Publication Number
WO 03/062035 A1

(51) International Patent Classification⁷: B62J 1/18

(21) International Application Number: PCT/US03/01416

(22) International Filing Date: 16 January 2003 (16.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/349,018 17 January 2002 (17.01.2002) US

(71) Applicant and

(72) Inventor: COHEN, Joshua, Dov [US/US]; 1002 F.
Kingswood Drive, Chapel Hill, NC 27517 (US).

(74) Agent: PROKOPETZ, Andrew, T.; Olive & Olive, P.A.,
PO Box 2049, Durham, NC 27702-2049 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,
SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: LOAD DEFORMABLE BICYCLE SEAT



(57) Abstract: A load deformable bicycle seat comprising a unique substantially flat posterior body section (PS) on which the rider sits, a unique load deformable elongated hollow nose section (NS), and a unique transition (TS) at the join of the body section (PS) to the nose section (NS) of the seat (20). The posterior section (PS) of the seat supports and is designed to promote pressure distribution around the ischeal tuberosities. The seat surface is substantially flat or shaped slightly concave to avoid pushing into the perineal region of the groin. The nose section (NS) comprises an integrated hollow tubular piece of deformable plastic, rubber, or the like having a rounded and sealed anterior portion (21).

WO 03/062035 A1